

## THANK YOU!

We'd like to sincerely thank you for purchasing your new vehicle mounting strap from Gum Creek Customs. The vehicle mount you have purchased is the world's first and only steering wheel handgun mount. Below is some information that will help you understand the product and its function. We hope that you enjoy your new product.

## GETTING STARTED

If needed later, this manual is available for download on our website in the event you lose or misplace it.

Package Contents:

Mounting Strap with coated hooks

Extra strap for BLACKHAWK! or other similar wide holsters

Adhesive hook strips (optional)



Gum Creek Customs, LLC  
Personal Defense Accessories  
Oxford, Georgia

Made in the USA

1-888-381-7872

info@gumcreekcustoms.com

## WARRANTY

Limited Lifetime Warranty. New Products are lifetime warranted to the original purchaser against failure of materials and workmanship. No other warranty applies. This warranty applies only if the product has not been damaged by accident, misuse or as a result of repair or modification. This warranty is not transferable. Gum Creek Customs reserves the right to make any design changes without notice or obligation to incorporate these changes in products previously purchased.

## INSTALLATION

Refer to diagram photos on opposite side if needed.

**Before proceeding, DO NOT attempt placing your holster onto the mount with a loaded firearm!** Doing so could result in serious injury or death.

1. Use any holster (sold separately) that has either a belt loop or clip. If your holster is not ambidextrous, then you will need a left handed holster to face the butt end of the gun right, or a right handed holster to face the butt end of the gun left.

\* If you plan to mount a BLACKHAWK! SERPA or similar wide holster, simply replace the top holster strap with the replacement strap provided, labeled, "BLACKHAWK! Strap".

Open both the wide upper Velcro loop and the lower Velcro loop that is smaller in width.

2. Pull the WIDE Velcro strip through the inside of the belt loop or clip of the holster as far as it will go. The wide Velcro loop is at the TOP of the mount. The small Velcro loop is at the BOTTOM and should not be used here. The wide Velcro strip can also be detached from the main part of the mount so that you can slightly adjust it vertically.
3. Pull with tension and wrap the wide strip, along with the holster, around the front of the main mounting strap.
4. Velcro the end of wide strip to the backside of the main mounting strap. Holster should now be snug on mounting strap.
5. The mount is now ready to position in your vehicle. Place the hook that is now above and behind your holster into the gap below your steering wheel column.
6. Place the bottom hook so it grabs onto the lower dash panel or somewhere in this area where it will allow you to tighten firmly.
7. Pull the strap down hard to tighten. You may need to gently lift up on the large buckle a little to allow the strap to slide. The strap material is heavy duty and is designed to not give easily. Continue to pull until mount is secure and tight. Now check and see if the mount is secure to your liking. Some very slight movement is fine, but you can remove the mount and use the adhesive hook strips to help reduce any horizontal movement if you want.
8. Once in place, you can either tuck any excess strap material behind the holster or dash, or you can cut it off with a pair of scissors or knife. We recommend leaving the excess if you plan on using the mount in another vehicle, because the dash length may vary. If you decide to cut, you will want to seal the cut end using a match or lighter to prevent fraying.

You can now loosely attach the lower Velcro loop strip around your holster. This small strip can be adjusted vertically on the back to where you want it, by simply pulling it off and putting it back on. You have a lot of vertical room to play with here depending on your holster length. You want to loosely attach for now, until you holster your firearm. Making it tight may make it more difficult to holster the firearm.

9. Your holster is now fully mounted and is ready to safely accept a firearm. Once you place your firearm in the holster, go back and tighten the lower Velcro strip, so it snugly fits around your holster. This will help reduce holster bounce or side-to-side holster movement while driving off-road.

To release the mount, simply reach under the enclosed metal support bar and lift up on the large buckle.

## DISCLAIMER

***You are responsible for knowing your local and state laws regarding firearms in your vehicle. Gum Creek is not responsible for you not knowing your laws. This includes firearm reciprocity, transporting, loaded/unloaded carry and vehicle open/concealed carry laws. While not required in all states, we highly recommend having a State Firearm's License and to check your laws if you are unsure before ordering. Gum Creek is also not responsible for any improper handling/use of your firearm(s) in conjunction with our products or any possible scenario's resulting within your vehicle due to an accident, theft, arrest, discharge, etc. Gum Creek cannot assume responsibility for ones intention of buying our products or for how one may or may not use safe and responsible gun control measures.***

Step 1



Step 4




Step 7



Step 2



Step 5



Step 8



Step 3



Step 6



Step 9



(Holster not included)